



WJB銅自潤軸承 (特殊規格尺寸可依圖訂製)

特殊銅合金系



自潤#500SP 止推墊圈(SPW)

尺 寸 (mm)		厚度T		公差 ⁻⁰ _{-0.1}		裝配孔			倒角		
內徑	外徑	3	5	7	8	10					
Ød	ØD	SPW	SPW	SPW	SPW	SPW	P.C.D	個數	使用埋頭螺栓	a	b
10.2	30	-1003					20	2	M3	1.5	0.3
12.2	40	-1203					28	"	"	2	0.4
12.2	40	-1203N					無埋頭螺栓孔			"	"
13.2	40	-1303					28	2	M3	"	"
14.2	40	-1403					"	"	"	"	"
15.2	50	-1503					35	"	"	"	"
16.2	50	-1603					"	"	"	"	"
16.2	50	-1603N					無埋頭螺栓孔			"	"
18.2	50	-1803					35	2	M3	"	"
20.2	50		-2005				"	"	M5	2.5	"
25.2	55		-2505				40	"	"	"	"
30.2	60		-3005				45	"	"	"	"
35.2	70		-3505				50	"	"	"	"
40.2	80			-4007			60	"	M6	3	0.5
45.2	90			-4507			70	"	"	"	"
50.3	100				-5008		75	4	"	4	0.6
55.3	110				-5508		85	"	"	"	"
60.3	120				-6008		90	"	M8	5	0.8
65.3	125				-6508		95	"	"	"	"
70.3	130					-7010	100	"	"	"	"
75.3	140					-7510	110	"	"	"	"
80.3	150					-8010	120	"	"	"	"
90.5	170					-9010	140	"	M10	"	"
100.5	190					-10010	160	"	"	"	"
120.5	200					-12010	175	"	"	"	"

- 請參考SPB組配。
- 可與SPB合併使用。

訂購型號

SPW -  
內徑 厚度